

ASTRON Ultima Universal 15W-40

Universal engine oil

Properties

ASTRON Ultima Universal 15W-40 is a universal SAE 15W-40 mineral engine oil offering excellent protection against wear and corrosion.

Specifications:

- API SF/CD

Use instructions

ASTRON Ultima Universal 15W-40 is recommended for use in diesel and petrol engines according to the manufacturer instructions. The SAE 15W-40 classification makes it suitable for year-round use under Central European weather conditions.

| TYPICAL PARAMETERS | METHODS | UNITS | ASTRON Ultima Universal 15W-40 |
|----------------------|-----------------|--------------------|--------------------------------|
| Density at 15°C | DIN 51 757 | kg/m ³ | 880 |
| Viscosity at 40°C | DIN EN ISO 3104 | mm ² /s | 96 |
| Viscosity at 100°C | DIN EN ISO 3104 | mm ² /s | 13,3 |
| Viscosity Index (VI) | DIN ISO 2909 | - | 144 |
| Viscosity at -20°C | ASTM D 5293 | mPa.s | 5460 |
| Pour point | DIN ISO 3016 | °C | -39 |
| COC flash point | DIN ISO 2592 | °C | 232 |
| Base Number | DIN ISO 3771 | mg KOH/g | 6,0 |

* meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.

17.06.2025



Power in every molecule

Duran Lubricants & Chemicals GmbH
Rodderheide 3-7 • D-33824 Werther

Tel. +49 5203 901510
www.astron-oil.de
info@durand-lub.com

Health, Safety and Environment –
information is provided for products
in the relevant Safety Data Sheet.

