

## ASTRON Galaxy VDP 5W-40

### Synthetic High-Performance Low-Friction Engine Oil for Passenger Cars

#### Properties

**ASTRON Galaxy VDP 5W-40** is a high-performance low-friction oil of viscosity class SAE 5W-40. Specially chosen base oils and additive systems give this engine oil its outstanding low-friction properties, based on excellent low-temperature viscosity, high thermal stability and low pumping work.

**ASTRON Galaxy VDP 5W-40** thus has a positive effect on fuel consumption.

#### Use instructions

**ASTRON Galaxy VDP 5W-40** has been specially developed for pump-nozzle injection systems from VW. These powerful diesel engines require an engine oil that meets particularly stringent performance criteria.

#### Specifications:

- ACEA A3/B4
- API SL/CF

#### Recommendations \*:

- VW 505.01
- Ford WSS-M2C 917-A

TYPICAL PARAMETERS	METHODS	UNITS	ASTRON Galaxy VDP 5W-40
Density at 15°C	DIN 51 757	kg/m <sup>3</sup>	857
Viscosity at 40°C	DIN 51 562	mm <sup>2</sup> /s	89
Viscosity at 100°C	DIN 51 562	mm <sup>2</sup> /s	14
Viscosity at -30°C	DIN 51 377	mPa.s	6200
Viscosity index (VI)	DIN ISO 2909	-	162
Pour point	DIN ISO 3016	°C	-48
COC flash point	DIN ISO 2592	°C	220
Base number	DIN ISO 3771	mg KOH/g	8,0
Sulphated ash	DIN 51 575	g/100 g	1,15

\* meets the requirements of the OEM manufacturer.  
The stated values may vary within the usual commercial range.

17.06.2025



**Power in every molecule**

Duran Lubricants & Chemicals GmbH  
Rodderheide 3-7 • D-33824 Werther

Tel. +49 5203 901510  
www.astron-oil.de  
info@durand-lub.com

Health, Safety and Environment –  
information is provided for products  
in the relevant Safety Data Sheet.

