

ASTRON Ultima Diesel Special 20W-50

Universal engine oil

Properties

ASTRON Ultima Diesel Special 20W-50 is a mineral oil based universal motor oil of viscosity class SAE 20W-50, with high wear and corrosion protection.

Use instructions

ASTRON Ultima Diesel Special 20W-50 is recommended for use in diesel engines according to the manufacturer instructions. The SAE 20W-50 classification makes it suitable for year-round use under Central European weather conditions.

Specifications:

- API CD

TYPICAL PARAMETERS	METHODS	UNITS	ASTRON Ultima Diesel Special 20W-50
Density at 15°C	DIN 51 757	kg/m ³	884
Viscosity at 40°C	DIN EN ISO 3104	mm ² /s	159
Viscosity at 100°C	DIN EN ISO 3104	mm ² /s	17,4
Viscosity index (VI)	DIN ISO 2909	-	118
Pour point	DIN ISO 3016	°C	-30
COC flash point	DIN ISO 2592	°C	256

* meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.

17.06.2025



Power in every molecule

Duran Lubricants & Chemicals GmbH
Rodderheide 3-7 • D-33824 Werther

Tel. +49 5203 901510
www.astron-oil.de
info@durand-lub.com

Health, Safety and Environment –
information is provided for products
in the relevant Safety Data Sheet.

