

ASTRON Galaxy VOL 0W-30

Synthetic high-performance low-friction engine oil for Volvo passenger car engines

Properties

ASTRON Galaxy VOL 0W-30 is a synthetic high-performance low-friction oil. Its low HTHS viscosity helps reduce fuel consumption during the cold start phase and in short-distance travel. Guarantees optimum wear protection and great engine cleanliness. The product is recommended for use in Volvo passenger cars with modern, high-efficiency Euro 4, 5 or 6 engines, with or without turbocharger, direct injection, multi-valve or hybrid technology.

ASTRON Galaxy VOL 0W-30 helps save fuel and reduces CO₂ emissions, thus protecting the environment.

Use instructions

ASTRON Galaxy VOL 0W-30 is recommended for modern gasoline and diesel engines with the specification VOLVO VCC 95200377.

Specifications:

- API SL
- ACEA A5/B5

Recommendation*:

- Volvo VCC 95200377

TYPICAL PARAMETERS	METHODS	UNITS	ASTRON Galaxy VOL 0W-30
Density at 15°C	DIN 51 757	kg/m ³	844
Viscosity at 40°C	DIN 51 562	mm ² /s	53,2
Viscosity at 100°C	DIN 51 562	mm ² /s	10,0
Viscosity index (VI)	DIN ISO 2909	-	180
Viscosity at -35°C	DIN 51 377	mPa.s	6000
COC flash point	DIN ISO 2592	°C	220
Pour point	DIN ISO 3016	°C	-39

* meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.

17.06.2025



Power in every molecule

Duran Lubricants & Chemicals GmbH
Rodderheide 3-7 • D-33824 Werther

Tel. +49 5203 901510
www.astron-oil.de
info@durand-lub.com

Health, Safety and Environment –
information is provided for products
in the relevant Safety Data Sheet.

