

## ASTRON Universal 2T Special

### Semi-synthetic two-stroke engine oil

#### Properties

- Semi-synthetic two-stroke engine oil.
- Excellent protection against rust, corrosion and wear.
- Continuous lubricant film preventing piston seizure and scoring.
- Protection against ring clogging.
- Residue-free combustion preventing spark arching.
- Suitable for use in systems with mixed or separate lubrication.
- Environmentally friendly thanks to extra low fume emissions.

#### Specifications:

- API TC
- ISO-L-EGD
- JASO FD

#### Use instructions

**ASTRON Universal 2T Special** is a semi-synthetic two-stroke engine oil designed for air-cooled and water-cooled two-stroke engines in cars, motorbikes, scooters and mopeds with separate or mixed lubrication, up to a mixing ratio of 1:50.

**Observe manufacturer instructions.**

TYPICAL PARAMETERS	METHODS	UNITS	ASTRON Universal 2T Special
Density at 15°C	DIN EN ISO 12185	kg/m <sup>3</sup>	871
Viscosity at 40°C	DIN ISO 51 562	mm <sup>2</sup> /s	63,6
Viscosity at 100°C	DIN ISO 51 562	mm <sup>2</sup> /s	9,2
Viscosity index (VI)	DIN ISO 2909	-	123
Pour point	ASTM D 7346	°C	-39
COC flash point	DIN ISO 2592	°C	164

\* meets the requirements of the OEM manufacturer.  
The stated values may vary within the usual commercial range.

17.06.2025



**Power in every molecule**

Duran Lubricants & Chemicals GmbH  
Rodderheide 3-7 • D-33824 Werther

Tel. +49 5203 901510  
www.astron-oil.de  
info@duran-oil.com

Health, Safety and Environment –  
information is provided for products  
in the relevant Safety Data Sheet.

