

ASTRON Brake Fluid DOT 4

Brake fluid

Properties

- Synthetic fluid.
- High dry and wet boiling point, reducing vapour bubble formation.
- Excellent protection for all metal parts in the brake system against corrosion.
- Good protection against wear and foaming.
- Compatible with all seals and hoses installed in the brake system.

Specifications:

- FMVSS 116 DOT 4
- SAE J 1703
- ISO 4925

Use instructions

ASTRON Brake Fluid DOT 4 is recommended for use in brake and clutch systems in vehicles that require a synthetic DOT 4 brake fluid.

ASTRON Brake Fluid DOT 4 can be mixed with all synthetic brake fluids of the same grade.

Special instructions:

- Store brake fluid only in sealed original container.
- Brake fluid can cause damage to vehicle paintwork.
- Observe manufacturer instructions!

TYPICAL PARAMETERS	METHODS	UNITS	ASTRON Brake Fluid DOT 4
Density at 20°C	ASTM D4052	g/cm ³	1.06
Viscosity at -40°C	SAE J1703 / 1704	mm ² /s	<1500
Dry boiling point (min.)	SAE J1703 / 1704	°C	>230
Wet boiling point (min.)	SAE J1703 / 1704	°C	>155

* meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.

17.06.2025



Power in every molecule

Duran Lubricants & Chemicals GmbH
Rodderheide 3-7 • D-33824 Werther

Tel. +49 5203 901510
www.astron-oil.de
info@duranduran-oil.com

Health, Safety and Environment –
information is provided for products
in the relevant Safety Data Sheet.

