

ASTRON Mehrzweckfett EP 2

Multi-purpose EP lithium complex grease

Properties

- Excellent adhesion on metal surfaces.
- Outstanding shear stability.
- EP additives reduce wear and increase load resistance.
- Water resistant.
- Prevents corrosion.
- Mixable with most conventional soap base grease products.

Use instructions

ASTRON Mehrzweckfett EP 2 is ideal for the lubrication of heavy-duty plain, anti-friction and wheel bearings, joints, chassis and bearing points exposed to impact and vibration stress. It is recommended for universal use in motor vehicles, construction machines, agricultural and forestry machinery operated in wet, dusty or dry environments.

When re-lubricating parts, ensure that the grease is not contaminated with dust or dirt particles.

Observe manufacturer instructions!

Specifications*:

- DIN 51 825: KP2K-30
- ISO/DIS 6743-9: ISO-L-XCCHB 2

Recommendations*:

- DTFR 33B120 (267.0)

TYPICAL PARAMETERS	METHODS	UNITS	ASTRON Mehrzweckfett EP 2
NLGI grade	DIN 51 818	-	2
Soap/thickener	-	-	lithium soap
Colour	visual	-	light brown
Texture	visual	-	flat
Operating temperature range	-	°C	-30 to +130
Penetration	DIN ISO 2137	0,1 mm	265-295
EMCOR test	ISO 51 802	Rating	0-0
Drop point	DIN ISO 2176	°C	>180
Viscosity (base oil) at 40°C	ASTM D 7042	mm ² /s	220

* meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.

17.06.2025



Power in every molecule

Duran Lubricants & Chemicals GmbH
Rodderheide 3-7 • D-33824 Werther

Tel. +49 5203 901510
www.astron-oil.de
info@duran-oil.com

Health, Safety and Environment –
information is provided for products
in the relevant Safety Data Sheet.



**MADE IN
GERMANY**