

ASTRON Sprint Turbo 15W-50

Universal high-performance engine oil

Properties

ASTRON Sprint Turbo 15W-50 is a multi-grade engine oil designed for year-round use. Engines with turbocharger and charge air cooling require oils that can withstand higher thermal and mechanical loads. Meet the requirements for such demanding operating conditions even at extended oil change intervals. It ensures reliable cold start at low ambient temperatures and proper lubrication at high operating temperatures. Thanks to the use of shear-resistant active agents, the product retains its SAE class 15W-50 properties over the entire oil change interval.

Use instructions

ASTRON Sprint Turbo 15W-50 is used in heavy-duty trucks, commercial and passenger cars with diesel engines, and in vehicles with petrol engines. Engine oils of this class are generally recommended where oil change intervals are extended.

Specifications:

- API CI-4
- API CF
- API SL

Recommendations*:

- MAN
- DAF
- Volvo
- Dongfeng
- FAW
- Foton
- Isuzu
- HOWO
- Shacman
- Hongyan

TYPICAL PARAMETERS	METHODS	UNITS	ASTRON Sprint Turbo 15W-50
SAE Class	DIN 51 511	-	15W-50
Density at 15°C	DIN 51 757	kg/m ³	875
Viscosity at 40°C	DIN 51 562	mm ² /s	126
Viscosity at 100°C	DIN 51 562	mm ² /s	17,6
Viscosity index (VI)	DIN ISO 2909	-	153
COC flash point	DIN ISO 2592	°C	>210
Pour point	DIN ISO 3016	°C	- 36

* meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.

17.06.2025



Power in every molecule

Duran Lubricants & Chemicals GmbH
Rodderheide 3-7 • D-33824 Werther

Tel. +49 5203 901510
www.astron-oil.de
info@durand-lub.com

Health, Safety and Environment –
information is provided for products
in the relevant Safety Data Sheet.

