

ASTRON LHM +

Special Hydraulic Fluid

Properties

- Extremely high viscosity index.
- Very low pour point.
- Excellent thermal stability.
- Very good corrosion protection
- Compatible with seals

Specifications*:

- PSA B71 2710 (Citroen/Peugeot)
- ISO 7308

Use instructions

ASTRON LHM + is a high-performance hydraulic fluid based on mineral oil for central hydraulic systems in PPE motor vehicles with specially marked green fluid reservoirs. Exceeds the performance level of previous LHM qualities.

Observe manufacturer instructions!

| TYPICAL PARAMETERS | METHODS | UNITS | ASTRON LHM + |
|----------------------|-------------|--------------------|-------------------|
| Density at 15°C | ASTM D 1298 | kg/m ³ | 845 |
| Viscosity at 40°C | ASTM D 445 | mm ² /s | 18 |
| Viscosity at 100°C | ASTM D 445 | mm ² /s | 6,3 |
| Viscosity index (VI) | ASTM D 2270 | - | 355 |
| Pourpoint | ASTM D 97 | °C | -62 |
| Colour | - | - | Fluorescent green |

* meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.

17.06.2025



Power in every molecule

Duran Lubricants & Chemicals GmbH
Rodderheide 3-7 • D-33824 Werther

Tel. +49 5203 901510
www.astron-oil.de
info@duran-oil.com

Health, Safety and Environment –
information is provided for products
in the relevant Safety Data Sheet.

