

ASTRON ATF MB 15

Low Viscosity Synthetic Automatic Transmission Fluid

Properties

- Reduced viscosity for maximum fuel economy
- High load capacity, outstanding wear minimisation
- Exceptional friction coefficient consistency
- No foaming
- High thermal stability
- Smooth gear shifting even at low temperatures
- Unrivalled viscosity-temperature behaviour
- Excellent oxidation stability
- No adverse effect on standard sealing materials

Recommendations*:

- MB 236.15

Use instructions

- Specially for the latest Mercedes-Benz 7-speed automatic transmission 722.9 with code A89, 7-speed automatic transmission hybrid 724.2, transfer cases in type 205, 213, 217, 218, 222, 238, 253, 257, 290 with transmission 725.0 and transfer cases in type 257 with transmission 725.1
- ATF MB 15 is not suitable for use in older Mercedes-Benz automatic transmissions and is not backward compatible

Observe manufacturer instructions!

TYPICAL PARAMETERS	METHODS	UNITS	ASTRON ATF MB 15
Density at 15°C	ASTM D4052	kg/m ³	847
Viscosity at 40°C	ASTM D445	mm ² /s	20,9
Viscosity at 100°C	ASTM D445	mm ² /s	4,81
Viscosity index (VI)	ASTM D2270	-	158
Pour point	ASTM D6892	°C	-42
COC flash point	ASTM D92	°C	178
Colour	-	-	blue

* meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.

17.06.2025



Power in every molecule

Duran Lubricants & Chemicals GmbH
Rodderheide 3-7 • D-33824 Werther

Tel. +49 5203 901510
www.astron-oil.de
info@duran-oil.com

Health, Safety and Environment –
information is provided for products
in the relevant Safety Data Sheet.

