

ASTRON SMT 75W-80 GL4

Partially Synthetic Gear Oil

Properties

ASTRON SMT 75W-80 GL4 is made of high quality mineral base oils and Synthetic base oils (PAO). In combination with a modern additive mix, a performance level for transmission oils is achieved.

- Excellent high pressure and anti-wear properties
- Good to very good corrosion and rust protection properties
- Low foaming and excellent aging stability
- High viscosity index and low pour point ensure comfortable operation switching even at lower temperatures
- Reduction of fuel consumption
- Extension of the oil change intervals

Use instructions

ASTRON SMT 75W-80 GL4 is used for the lubrication of synchronized and non-synchronized gearboxes. It is particularly recommended for commercial vehicles equipped with ZF gearboxes, and are especially suitable for mechanical transmissions and steering systems with re/intarders.

Specifications:

- API GL-4

Recommendations*:

- IVECO
- Volvo 97307
- DAF
- ZF TE-ML 01L, 02L08, 13, 18K, 24A
- MAN 341 Typ Z-4
- Eaton Extended Drain (300,000 km)
- Renault (in accordance with Renault note technique B0032/2 Annex 3)

TYPICAL PARAMETERS	METHODS	UNITS	ASTRON SMT 75W-80 GL 4
SAE Class		-	75W-80
Density at 15°C	DIN 51 757	kg/m ³	854
Viscosity at 40°C	DIN 51 562	mm ² /s	50,4
Viscosity at 100°C	DIN 51 562	mm ² /s	8,7
Viscosity index (VI)	DIN ISO 2909	-	151
Pourpoint	DIN ISO 3016	°C	- 39
Flash point COC	DIN ISO 2592	°C	228

* meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.

17.06.2025



Power in every molecule

Duran Lubricants & Chemicals GmbH
Rodderheide 3-7 • D-33824 Werther

Tel. +49 5203 901510
www.astron-oil.de
info@durand-lub.com

Health, Safety and Environment –
information is provided for products
in the relevant Safety Data Sheet.

