

ASTRON ATF MB 17

Low Viscosity Synthetic Automatic Transmission Fluid

Properties

- excellent fuel economy
- excellent lubricity
- very high thermal stability
- high, stable viscosity index
- very good oxidation stability
- Protection against wear, corrosion and foam formation
- excellent cooling capacity
- excellent frictional stability

Recommendation*:

- MB 236.17

Application notes

- Especially for the latest Mercedes-Benz 9-speed automatic transmissions (9G-Tronic) 725.0 / 725.1 and 4MATIC
- **ASTRON ATF MB 17** also meets the specifications of MB 236.16.
- **ASTRON ATF MB 17** cannot be used in older Mercedes-Benz automatic transmissions and is not downwards compatible with MB-Approval MB 236.10, MB 236.12, MB 236.14, MB 236.15

Observe manufacturer's instructions!

TYPICAL PARAMETERS	METHODS	UNITS	ASTRON ATF MB 17
Viscosity at 15°C	ASTM D4052	kg/m ³	848
Viscosity 40°C	ASTM D445	mm ² /s	22,15
Viscosity 100°C	ASTM D445	mm ² /s	5
Viscosity index (VI)	ASTM D2270	-	162
Pour point	ASTM D6892	°C	-42
Flash point COC	ASTM D92	°C	>180
Colour	-	-	yellow

* meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.

17.06.2025



Power in every molecule

Duran Lubricants & Chemicals GmbH
Rodderheide 3-7 • D-33824 Werther

Tel. +49 5203 901510
www.astron-oil.de
info@durand-lub.com

Health, Safety and Environment –
information is provided for products
in the relevant Safety Data Sheet.

