

## ASTRON Ultima Balance 15W-40

### High-performance universal engine oil

#### Properties

**ASTRON Ultima Balance 15W-40** is a mineral high-performance universal engine oil of viscosity class SAE 15W-40.

Base oils produced with the latest refinery technology and carefully selected innovative additives guarantee that the product meets the highest requirements. Among its most outstanding properties are the excellent shear stability at high temperatures and exceptional wear protection under all operating conditions. Cleaning additives prevent deposits, keep pistons and valves clean and protect the engine against black sludge. Clean engines and low friction reduce energy loss in the engine and minimise servicing costs.

#### Use instructions

**ASTRON Ultima Balance 15W-40** is a high-performance motor oil, universally applicable, even at high loads. Its performance spectrum covers the requirements of passenger car, petrol and diesel engines with and without turbocharging.

The high requirements of modern, low-consumption engines to meet the tightened exhaust emission standards are met with reserve.

#### Specifications:

- ACEA A3/B4
- API SL/CF

#### Recommendations\*:

- MB 229.1
- VW 505.00

TYPICAL PARAMETERS	METHODS	UNITS	ASTRON Ultima Balance 15W-40
Density at 15°C	DIN 51 757	kg/m <sup>3</sup>	861
Viscosity at 40°C	DIN 51 562	mm <sup>2</sup> /s	97
Viscosity at 100°C	DIN 51 562	mm <sup>2</sup> /s	14,7
Viscosity index (VI)	DIN ISO 2909	-	158
Viscosity at -20°C	DIN 51 377	mPa.s	5380
Pour point	DIN ISO 3016	°C	-42
Flash point COC	DIN ISO 2592	°C	230
Total base number	DIN ISO 3771	mg KOH/g	10,1

\* meets the requirements of the OEM manufacturer.

The stated values may vary within the usual commercial range.

17.06.2025



**Power in every molecule**

Duran Lubricants & Chemicals GmbH  
Rodderheide 3-7 • D-33824 Werther

Tel. +49 5203 901510  
www.astron-oil.de  
info@duran-oil.com

Health, Safety and Environment –  
information is provided for products  
in the relevant Safety Data Sheet.

