

ASTRON Universal 2T

Two-stroke engine oil

Properties

- Mineral two-stroke engine oil.
- Good protection against rust, corrosion and wear.
- Continuous lubricant film preventing piston seizure and scoring.
- Protection against deposits and spark arching.
- Suitable for use in systems with mixed or separate lubrication.
- Environmentally friendly thanks to low fume emissions.

Specifications

- API TC
- ISO-L-EGD
- JASO FB

Use instructions

ASTRON Universal 2T is a universal two-stroke engine oil for air and water cooled two-stroke engines in small motorbikes, scooters and mopeds with separate or mixed lubrication, up to a mixing ratio of 1:50.

Observe manufacturer instructions.

TYPICAL PARAMETERS	METHODS	UNITS	ASTRON Universal 2T
Density at 15°C	DIN EN ISO 12185	kg/m ³	878
Viscosity at 40°C	DIN ISO 51 562	mm ² /s	63,6
Viscosity at 100°C	DIN ISO 51 562	mm ² /s	8,6
Viscosity index (VI)	DIN ISO 2909	-	108
Pour point	ASTM D 7346	°C	-24
COC flash point	DIN ISO 2592	°C	141

* meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.

17.06.2025



Power in every molecule

Duran Lubricants & Chemicals GmbH
Rodderheide 3-7 • D-33824 Werther

Tel. +49 5203 901510
www.astron-oil.de
info@durand-lub.com

Health, Safety and Environment –
information is provided for products
in the relevant Safety Data Sheet.

