

ASTRON Tractor Oil STOU 10W-30

Super Universal Tractor Oil STOU

Properties

High-quality base oils and additives tailor-made to meet the high demands of modern farming ensure excellent properties under tough operating conditions. **ASTRON Tractor Oil STOU 10W-30**

- Is suitable for year-round use.
- Reduces wear in all units even after short lubrication time.
- Offers high temperature safety.
- Reduces fuel and oil consumption, thus protecting the environment.
- Has an excellent dirt dispersing capacity and prevents sludge.
- Prolongs the service life of the engine.
- Allows for extended oil change intervals.

Use instructions

ASTRON Tractor Oil STOU 10W-30 is the ideal oil for modern tractors. Using the same products for engines, transmissions and hydraulic systems prevents confusion of oils and helps reducing costs.

ASTRON Tractor Oil STOU 10W-30 is also suitable for wet brakes and clutches (PTO clutches).

Specifications:

- API CG-4/SF
- API GL-4

STOU*:

- ZF TE-ML 03A/05K/06B/06C/07B/07D
- Massey Fergusson M1145/M1144/M1139
- Ford M2C159 B/C
- New Holland NH030C/82009201
- John Deere J27

UTTO*:

- Massey Fergusson M1135
- New Holland NH410B
- John Deere J27C
- Allison C4 (level)
- Ford M2C86B/M2C134D
- Caterpillar TO-2 (level)

Hydraulik*:

- Sperry Vickers/Eaton M29505, I-280-S
- Sauer Sunstrand/Danfoss Hydrostatic Trans Fluid

TYPICAL PARAMETERS	METHODS	UNITS	ASTRON Tractor Oil STOU 10W-30
Density at 15°C	DIN 51 757	kg/m³	868
Viscosity at 40°C	DIN 51 562	mm²/s	68,7
Viscosity at 100°C	DIN 51 562	mm²/s	10,5
Viscosity index (VI)	DIN ISO 2909	-	139
Viscosity at -25°C	DIN 51 377	mPa.s	6300
Pourpoint	DIN ISO 3016	°C	-48
Flash point COC	DIN ISO 2592	°C	>220
TBN	DIN ISO 3771	mg KOH/g	11,0

* meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.

17.06.2025



Power in every molecule

Duran Lubricants & Chemicals GmbH
Rodderheide 3-7 • D-33824 Werther

Tel. +49 5203 901510
www.astron-oil.de
info@duran-oil.com

Health, Safety and Environment –
information is provided for products
in the relevant Safety Data Sheet.

