

ASTRON Brake Fluid DOT 4 LV

Low-viscosity high-performance brake fluid

Properties

- Low viscosity guarantees perfect functioning of systems.
- Synthetic fluid.
- Excellent thermal stability.
- Optimum protection for all metal parts in the brake system against corrosion.
- Unrivalled oxidation stability and optimised hygroscopic properties ensure high safety margin.
- Compatible with all seals and hoses installed in the brake system.

Use instructions

ASTRON Brake Fluid DOT 4 LV has been specially designed for use in heavy-duty brake systems of vehicles that require a DOT 4 synthetic brake fluid. The product is particularly recommended for brake systems with **ESP/DSC, ASR and ABS**. **ASTRON Brake Fluid DOT 4 LV** can be mixed with all synthetic brake fluids of the same grade.

Special instructions:

- Store brake fluid only in sealed original container.
- Brake fluid can cause damage to vehicle paintwork.
- Observe manufacturer instructions!

Specifications

- FMVSS 116 DOT 3 / DOT 4
- SAE J 1703 / J 1704
- ISO 4925 Class 6

Recommendation*:

- VW TL 766-Z, VW 50 114
- BMW QV 34 001
- GM Europa GMW 3356
- PSA STL S71 2114
- Ford WSS-M6C65-A2

TYPICAL PARAMETERS	METHODS	UNITS	ASTRON Brake Fluid DOT 4 LV
Density at 20°C	DIN 51 757	g/cm³	1,06
Viscosity at - 40°C	SAE J1703 / 1704	mm²/s	Max. 700
Dry boiling point (min.)	SAE J1703 / 1704	°C	265
Wet boiling point (min.)	SAE J1703 / 1704	°C	170

* meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.

17.06.2025



Power in every molecule

Duran Lubricants & Chemicals GmbH
Rodderheide 3-7 • D-33824 Werther

Tel. +49 5203 901510
www.astron-oil.de
info@duran-oil.com

Health, Safety and Environment –
information is provided for products
in the relevant Safety Data Sheet.

