

ASTRON Galaxy VSi 5W-40

Synthetic High-Performance Low-Friction Engine Oil for Passenger Cars

Properties

ASTRON Galaxy VSi 5W-40 is a synthetic high-performance engine oil of SAE class 5W-40. Synthetic components combined with carefully selected innovative additives guarantee that the product meets the latest requirements. Thanks to the significantly improved engine oil quality, **ASTRON Galaxy VSi 5W-40** offers further enhanced wear protection and keeps the engine perfectly clean, even at extended oil change intervals. The extremely low cold viscosity of the lubricant and its reliable high-temperature viscosity properties guarantee significant reduction in fuel consumption.

Use instructions

ASTRON Galaxy VSi 5W-40 is the ideal high-performance low-friction engine oil for demanding engines. It is used in petrol and diesel engines in passenger cars, including models with turbocharger and direct injection and is recommended for all operating conditions.

Specifications:

- ACEA A3/B4
- API SN/CF

Approval:

MB-Approval 229.3

Recommendations*:

- VW 502.00/505.00
- BMW Longlife-01
- Porsche A40
- Renault RN 0700/RN 0710
- Opel GM-LL-B-025
- Fiat 9.55535-M2
- PSA B71 2296

TYPICAL PARAMETERS	METHODS	UNITS	ASTRON Galaxy VSi 5W-40
Density at 15°C	DIN 51 757	kg/m³	853
Viscosity at 40°C	DIN 51 562	mm²/s	93,1
Viscosity at 100°C	DIN 51 562	mm²/s	15,4
Viscosity index (VI)	DIN ISO 2909	-	176
Viscosity at -30°C	DIN 51 377	mPa.s	5960
Pour point	DIN ISO 3016	°C	-39
COC flash point	DIN ISO 2592	°C	226
TBN	DIN ISO 3771	mg KOH/g	9,8

^{*} meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.

17.06.2025





