

Safety Data Sheet

ASTRON Synthetic 75W-140 LS

Revision date: 14.01.2022

Page 1 of 16

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ASTRON Synthetic 75W-140 LS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

gear oil

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Company name:	Duran Lubricants & Chemicals GmbH	
Street:	Rodderheide 3-7	
Place:	D-33824 Werther	
Telephone:	+49 (0)5203-901510	Fax: +49 (0)5203-901515
e-mail:	info@durand-oil.com	
Internet:	www.fosser.de	
Responsible Department:	Produktsicherheit / Product Safety	
	info@durand-oil.com	

1.4. Emergency telephone number:

Giftinformationszentrum Nord
(Göttingen)+49 (0)551/19240

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Respiratory or skin sensitisation: Skin Sens. 1

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

May cause an allergic skin reaction.

Harmful to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

C10-14-tert-Alkylamines

phenol, (tetrapropenyl) derivatives

Signal word: Warning

Pictograms:



Hazard statements

H317

May cause an allergic skin reaction.

H412

Harmful to aquatic life with long lasting effects.

Precautionary statements

P261

Avoid breathing dust/fume/gas/mist/vapours/spray.

Safety Data Sheet

ASTRON Synthetic 75W-140 LS

Revision date: 14.01.2022

Page 2 of 16

P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P302+P352	IF ON SKIN: Wash with plenty of Water and soap.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P501	Dispose of contents / container in accordance with official regulations.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified			36 - < 60,84 %
	265-157-1	649-467-00-8	01-2119484627-25	
	Asp. Tox. 1; H304			
	C10-14-tert-Alkylamines			0 - < = 0,62 %
	701-175-2		01-2119456798-18	
	Acute Tox. 2, Acute Tox. 3, Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1A, STOT SE 3, Aquatic Acute 1, Aquatic Chronic 1; H330 H311 H302 H314 H318 H317 H335 H400 H410			
84418-71-3	Phosphoric acid, mono- and bis(branched and linear pentyl) esters			0 - < = 0,4 %
	282-784-6		01-2119979550-30	
	Skin Corr. 1B, Eye Dam. 1, Aquatic Chronic 3; H314 H318 H412			
91648-65-6	1,3,4-Thiadiazolidine-2,5-dithione, reaction products with hydrogen peroxide and tert-nonanethiol			0 - < = 0,2 %
	293-927-7		01-2119976351-35	
	Aquatic Chronic 3; H412			
1213789-63-9	C16-18-(even numbered, saturated and unsaturated)-alkylamines			0 - < = 0,12 %
	627-034-4		01-2119473797-19	
	Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Acute 1, Aquatic Chronic 1; H302 H314 H318 H335 H373 H304 H400 H410			
74499-35-7	phenol, (tetrapropenyl) derivatives			0 - < 0,02 %
		604-092-00-9		
	Repr. 1B, Skin Corr. 1C, Eye Dam. 1, Aquatic Acute 1, Aquatic Chronic 1; H360F H314 H318 H400 H410			

Full text of H and EUH statements: see section 16.

Safety Data Sheet

ASTRON Synthetic 75W-140 LS

Revision date: 14.01.2022

Page 3 of 16

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64742-54-7	265-157-1	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified	36 - < 60,84 %
		inhalation: LC50 = 5,53 mg/l (dusts or mists); dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
	701-175-2	C10-14-tert-Alkylamines	0 - < = 0,62 %
		inhalation: LC50 = >= 157 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); dermal: LD50 = 251 mg/kg; oral: LD50 = > 500 mg/kg	
84418-71-3	282-784-6	Phosphoric acid, mono- and bis(branched and linear pentyl) esters	0 - < = 0,4 %
		oral: LD50 = > 2000 - < 5000 mg/kg	
91648-65-6	293-927-7	1,3,4-Thiadiazolidine-2,5-dithione, reaction products with hydrogen peroxide and tert-nonanethiol	0 - < = 0,2 %
		inhalation: LC50 = > 2,75 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 10000 mg/kg	
1213789-63-9	627-034-4	C16-18-(even numbered, saturated and unsaturated)-alkylamines	0 - < = 0,12 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = 1689 mg/kg M akut; H400: M=10 M chron.; H410: M=10	
74499-35-7		phenol, (tetrapropenyl) derivatives	0 - < 0,02 %
		dermal: LD50 = >2000 mg/kg; oral: LD50 = >2000 mg/kg M akut; H400: M=10 M chron.; H410: M=10	

Further Information

phenol, (tetrapropenyl) derivatives: This substance has been listed as SVHC (substance of very high concern) in the Candidate List according to Article 59 of REACH.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove affected person from the danger area and lay down.
 Do not leave affected person unattended.
 In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

Remove person to fresh air and keep comfortable for breathing.
 In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap.
 Take off contaminated clothing and wash it before reuse.
 In case of skin irritation, consult a physician.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Rinse mouth thoroughly with water.
 Let water be drunken in little sips (dilution effect).
 Do NOT induce vomiting.
 In all cases of doubt, or when symptoms persist, seek medical advice.

Safety Data Sheet

ASTRON Synthetic 75W-140 LS

Revision date: 14.01.2022

Page 4 of 16

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Use water spray jet to protect personnel and to cool endangered containers.
Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

In case of fire may be liberated:

- Carbon monoxide (CO)
- Carbon dioxide (CO₂).
- Nitrogen oxides (NO_x)
- Pyrolysis products, toxic

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Use of protective clothing
In case of fire and/or explosion do not breathe fumes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

Keep people at a distance and stay on the windward side.
Special danger of slipping by leaking/spilling product.

For non-emergency personnel

Wear protective gloves/protective clothing and eye/face protection.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.
Do not allow to enter into soil/subsoil.
Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

For containment

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.
Remove from the water surface (e.g. skimming, sucking).

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8

Safety Data Sheet

ASTRON Synthetic 75W-140 LS

Revision date: 14.01.2022

Page 5 of 16

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

- Avoid formation of oil dust.
- Use personal protection equipment.
- Do not put any product-impregnated cleaning rags into your trouser pockets.
- Clear spills immediately.

Advice on protection against fire and explosion

- No special fire protection measures are necessary.
- Take precautionary measures against static discharges.
- Keep away from sources of ignition - No smoking.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

- Keep container tightly closed and in a well-ventilated place.
- Keep only in the original container. Store in a cool dry place. (Protect from moisture.)
- Floors should be impervious, resistant to liquids and easy to clean.

Hints on joint storage

- Do not store together with:
 - Materials capable of ignition under almost all normal temperature conditions
 - Explosives

7.3. Specific end use(s)

gear oil

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Safety Data Sheet

ASTRON Synthetic 75W-140 LS

Revision date: 14.01.2022

Page 6 of 16

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
DNEL type				
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified			
Worker DNEL, long-term	inhalation	systemic		2,73 mg/m ³
Worker DNEL, long-term	inhalation	local		5,58 mg/m ³
Worker DNEL, long-term	dermal	systemic		0,97 mg/kg bw/day
Consumer DNEL, long-term	inhalation	local		1,19 mg/m ³
Consumer DNEL, long-term	oral	systemic		0,74 mg/kg bw/day
	C10-14-tert-Alkylamines			
Worker DNEL, long-term	inhalation	systemic		12,5 mg/m ³
Worker DNEL, long-term	inhalation	local		12,1 mg/m ³
Consumer DNEL, long-term	inhalation	systemic		2,5 mg/m ³
Consumer DNEL, long-term	inhalation	local		1,2 mg/m ³
Consumer DNEL, long-term	oral	systemic		0,35 mg/kg bw/day
91648-65-6	1,3,4-Thiadiazolidine-2,5-dithione, reaction products with hydrogen peroxide and tert-nonanethiol			
Worker DNEL, long-term	inhalation	systemic		4,408 mg/m ³
Worker DNEL, long-term	dermal	systemic		6,25 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic		1,087 mg/m ³
Consumer DNEL, long-term	dermal	systemic		3,125 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic		0,625 mg/kg bw/day
1213789-63-9	C16-18-(even numbered, saturated and unsaturated)-alkylamines			
Worker DNEL, long-term	inhalation	systemic		0,38 mg/m ³
Worker DNEL, long-term	inhalation	local		1 mg/m ³
Worker DNEL, acute	inhalation	local		1 mg/m ³
Consumer DNEL, long-term	inhalation	systemic		0,035 mg/m ³
Consumer DNEL, long-term	oral	systemic		0,04 mg/kg bw/day

Safety Data Sheet

ASTRON Synthetic 75W-140 LS

Revision date: 14.01.2022

Page 7 of 16

PNEC values

CAS No	Substance	
	Environmental compartment	Value
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified	
	Secondary poisoning	9,33 mg/kg
	C10-14-tert-Alkylamines	
	Freshwater	0,001 mg/l
	Freshwater (intermittent releases)	0,004 mg/l
	Marine water	0 mg/l
	Freshwater sediment	2,14 mg/kg
	Marine sediment	0,214 mg/kg
	Secondary poisoning	4,71 mg/kg
	Micro-organisms in sewage treatment plants (STP)	0,635 mg/l
	Soil	0,428 mg/kg
84418-71-3	Phosphoric acid, mono- and bis(branched and linear pentyl) esters	
	Freshwater	0,056 mg/l
	Freshwater (intermittent releases)	0,56 mg/l
	Marine water	0,0056 mg/l
	Freshwater sediment	2,03 mg/kg
	Marine sediment	0,203 mg/kg
	Micro-organisms in sewage treatment plants (STP)	100 mg/l
	Soil	0,373 mg/kg
91648-65-6	1,3,4-Thiadiazolidine-2,5-dithione, reaction products with hydrogen peroxide and tert-nonanethiol	
	Freshwater	0,041 mg/l
	Freshwater (intermittent releases)	0,41 mg/l
	Marine water	0,004 mg/l
	Freshwater sediment	380,62 mg/kg
	Marine sediment	38,06 mg/kg
	Secondary poisoning	6,67 mg/kg
	Micro-organisms in sewage treatment plants (STP)	8000 mg/l
	Soil	308,96 mg/kg
1213789-63-9	C16-18-(even numbered, saturated and unsaturated)-alkylamines	
	Freshwater	0,00026 mg/l
	Freshwater (intermittent releases)	0,0016 mg/l
	Marine water	0,000026 mg/l
	Freshwater sediment	3,76 mg/kg
	Marine sediment	0,376 mg/kg
	Micro-organisms in sewage treatment plants (STP)	0,55 mg/l
	Soil	10 mg/kg

Safety Data Sheet

ASTRON Synthetic 75W-140 LS

Revision date: 14.01.2022

Page 8 of 16

Additional advice on limit values

To date, no national critical limit values exist.

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Protective and hygiene measures

Take off contaminated clothing and wash it before reuse.

Wash hands before breaks and after work.

When using do not eat, drink, smoke, sniff.

Eye/face protection

During filling, metering, mixing and sampling must be used:

Wear eye/face protection. DIN EN 166

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Recommended glove articles: EN ISO 374

Suitable material: NBR (Nitrile rubber)

Thickness of the glove material: 0,4 mm

Breakthrough times and swelling properties of the material must be taken into consideration. Breakthrough time: > 8h

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	yellow
Odour:	characteristic
Odour threshold:	not determined
pH-Value:	not determined

Changes in the physical state

Melting point:	not determined
Boiling point or initial boiling point and boiling range:	not determined
Pour point:	-45 °C
Flash point:	218 °C

Safety Data Sheet

ASTRON Synthetic 75W-140 LS

Revision date: 14.01.2022

Page 9 of 16

Flammability

Solid/liquid: not applicable

Gas: not applicable

Explosive properties

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Lower explosion limits: not determined

Upper explosion limits: not determined

Self-ignition temperature

Solid: not applicable

Gas: not applicable

Decomposition temperature: not determined

Oxidizing properties

The product is not: oxidising.

Vapour pressure: not determined

Density (at 15 °C): 0,874 g/cm³

Water solubility: not determined

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined

Viscosity / dynamic: not determined

Viscosity / kinematic:
(at 40 °C) 151,5 mm²/s

Relative vapour density: not determined

Evaporation rate: not determined

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

The formation of combustible vapours is possible at temperatures above: Flash point

10.4. Conditions to avoid

Avoid: Thermal decomposition

10.5. Incompatible materials

Materials to avoid:

- Oxidising agent
- Reducing agent

10.6. Hazardous decomposition products

Hazardous combustion products:

Safety Data Sheet

ASTRON Synthetic 75W-140 LS

Revision date: 14.01.2022

Page 10 of 16

- Carbon monoxide (CO)
- Carbon dioxide (CO₂).
- Nitrogen oxides (NO_x)
- Pyrolysis products, toxic

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 > 5000 mg/kg	Rabbit	Study report (1982)	OECD Guideline 402
	inhalation (4 h) aerosol	LC50 5,53 mg/l	Rat		OECD Guideline 403
	C10-14-tert-Alkylamines				
	oral	LD50 > 500 mg/kg	Rat	Study report (1993)	OECD Guideline 401
	dermal	LD50 251 mg/kg	Rat	Study report (1993)	OECD Guideline 402
	inhalation (4 h) vapour	LC50 ≥ 157 mg/l	Rat	Study report (2001)	OECD Guideline 403
	inhalation aerosol	ATE 0,05 mg/l			
84418-71-3	Phosphoric acid, mono- and bis(branched and linear pentyl) esters				
	oral	LD50 > 2000 - < 5000 mg/kg	Rat	Study report (2012)	OECD Guideline 423
91648-65-6	1,3,4-Thiadiazolidine-2,5-dithione, reaction products with hydrogen peroxide and tert-nonanethiol				
	oral	LD50 > 10000 mg/kg	Rat	Study report (1981)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rabbit	Study report (1981)	OECD Guideline 402
	inhalation (4 h) vapour	LC50 > 2,75 mg/l	Rat	Study report (1981)	OECD Guideline 403
1213789-63-9	C16-18-(even numbered, saturated and unsaturated)-alkylamines				
	oral	LD50 1689 mg/kg	Rat	Study report (1993)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1985)	OECD Guideline 402
74499-35-7	phenol, (tetrapropenyl) derivatives				
	oral	LD50 > 2000 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg			

Safety Data Sheet

ASTRON Synthetic 75W-140 LS

Revision date: 14.01.2022

Page 11 of 16

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (C10-14-tert-Alkylamines)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

The product contains less than 3% DMSO extract (method IP346). A classification as a carcinogen with R45 is deleted. (Note L)

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

Safety Data Sheet

ASTRON Synthetic 75W-140 LS

Revision date: 14.01.2022

Page 12 of 16

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified					
	Acute fish toxicity	LL50 > 100 mg/l	96 h	Pimephales promelas	Study report (1995)	OECD Guideline 203
	C10-14-tert-Alkylamines					
	Acute fish toxicity	LC50 1,3 mg/l	96 h	Oncorhynchus mykiss	Study report (1994)	OECD Guideline 203
	Acute algae toxicity	ErC50 0,44 mg/l	72 h	Pseudokirchneriella subcapitata	Study report (1994)	OECD Guideline 201
	Acute crustacea toxicity	EC50 4,1 mg/l	48 h	Daphnia magna	Study report (1984)	OECD Guideline 202
	Fish toxicity	NOEC 0,078 mg/l	96 d	Oncorhynchus mykiss	Study report (2002)	OECD Guideline 210
	Acute bacteria toxicity	(63,5 mg/l)	0,5 h	activated sludge of a predominantly domestic sewage	Study report (2008)	OECD Guideline 209
84418-71-3	Phosphoric acid, mono- and bis(branched and linear pentyl) esters					
	Acute fish toxicity	LC50 > 100 mg/l	96 h	Oncorhynchus mykiss	Study report (2012)	OECD Guideline 203
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Pseudokirchneriella subcapitata	Study report (2012)	OECD Guideline 201
	Acute crustacea toxicity	EC50 56 mg/l	48 h	Daphnia magna	Study report (2012)	OECD Guideline 202
	Acute bacteria toxicity	(> 1000 mg/l)	3 h	activated sludge of a predominantly domestic sewage	Study report (2012)	OECD Guideline 209
91648-65-6	1,3,4-Thiadiazolidine-2,5-dithione, reaction products with hydrogen peroxide and tert-nonanethiol					
	Acute fish toxicity	LL50 > 1000 mg/l	96 h	Pimephales promelas	Study report (1985)	OECD Guideline 203
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Pseudokirchneriella subcapitata	Study report (2012)	OECD Guideline 201
	Acute crustacea toxicity	EL50 < 100 mg/l	48 h	Daphnia magna	Study report (2005)	OECD Guideline 202
1213789-63-9	C16-18-(even numbered, saturated and unsaturated)-alkylamines					
	Acute fish toxicity	LC50 0,84 mg/l	96 h	Danio rerio	Study report (2006)	OECD Guideline 203
	Acute algae toxicity	ErC50 0,39 mg/l	72 h	Desmodesmus subspicatus	Study report (2002)	OECD Guideline 201
	Acute crustacea toxicity	EC50 0,32 mg/l	48 h	Daphnia magna	Study report (2006)	OECD Guideline 202
	Crustacea toxicity	NOEC 0,013 mg/l	21 d	Daphnia magna	Study report (2002)	OECD Guideline 211
	Acute bacteria toxicity	(32 mg/l)	3 h	activated sludge of a predominantly domestic sewage	Study report (1989)	OECD Guideline 209
74499-35-7	phenol, (tetrapropenyl) derivatives					
	Acute fish toxicity	LC50 40 mg/l	96 h			

Safety Data Sheet

ASTRON Synthetic 75W-140 LS

Revision date: 14.01.2022

Page 13 of 16

	Acute crustacea toxicity	EC50 mg/l	0,037	48 h			
	Algae toxicity	NOEC mg/l	0,07	3 d			
	Crustacea toxicity	NOEC mg/l	0,0037	3 d			

12.2. Persistence and degradability

Not readily biodegradable (according to OECD criteria)

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
	C10-14-tert-Alkylamines	2,9
84418-71-3	Phosphoric acid, mono- and bis(branched and linear pentyl) esters	< -1,94
1213789-63-9	C16-18-(even numbered, saturated and unsaturated)-alkylamines	5,16

BCF

CAS No	Chemical name	BCF	Species	Source
91648-65-6	1,3,4-Thiadiazolidine-2,5-dithione, reaction products with hydrogen peroxide and tert-nonanethiol	15,7	Fish, not further specified.	Study report (2013)
1213789-63-9	C16-18-(even numbered, saturated and unsaturated)-alkylamines	173		Environmental Toxico
74499-35-7	phenol, (tetrapropenyl) derivatives	1601		

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

Safety Data Sheet

ASTRON Synthetic 75W-140 LS

Revision date: 14.01.2022

Page 14 of 16

<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.
Inland waterways transport (ADN)	
<u>14.1. UN number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.
Marine transport (IMDG)	
<u>14.1. UN number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.
Air transport (ICAO-TI/IATA-DGR)	
<u>14.1. UN number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.
<u>14.5. Environmental hazards</u>	
ENVIRONMENTALLY HAZARDOUS:	No
<u>14.6. Special precautions for user</u>	
No dangerous good in sense of this transport regulation.	
<u>14.7. Maritime transport in bulk according to IMO instruments</u>	
No dangerous good in sense of this transport regulation.	

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 30

 Information according to 2012/18/EU
 (SEVESO III):

Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D):

2 - obviously hazardous to water

Skin resorption/Sensitization:

Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2,3,4,5,6,7,8,9,10,11,12,15,16.

Safety Data Sheet

ASTRON Synthetic 75W-140 LS

Revision date: 14.01.2022

Page 15 of 16

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%
CLP: Classification, labelling and Packaging
REACH: Registration, Evaluation and Authorization of Chemicals
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
UN: United Nations
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration
ATE: Acute toxicity estimate
LL50: Lethal loading, 50%
EL50: Effect loading, 50%
EC50: Effective Concentration 50%
ErC50: Effective Concentration 50%, growth rate
NOEC: No Observed Effect Concentration
BCF: Bio-concentration factor
PBT: persistent, bioaccumulative, toxic
vPvB: very persistent, very bioaccumulative
RID: Regulations concerning the international carriage of dangerous goods by rail
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)
EmS: Emergency Schedules
MFAG: Medical First Aid Guide
ICAO: International Civil Aviation Organization
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
IBC: Intermediate Bulk Container
VOC: Volatile Organic Compounds
SVHC: Substance of Very High Concern
For abbreviations and acronyms, see table at <http://abbrev.esdscom.eu>

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.

Safety Data Sheet

ASTRON Synthetic 75W-140 LS

Revision date: 14.01.2022

Page 16 of 16

H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H360F	May damage fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)