

ASTRON ZHF-M

Mineral Central Hydraulic Fluid

Properties

- High viscosity index
- Excellent corrosion protection
- Very low pour point
- No foaming
- Outstanding thermal stability
- Reliable friction coefficient characteristic
- Unrivalled viscosity-temperature behaviour
- Excellent oxidation stability
- No adverse effect on standard sealing materials

Recommendations*:

- MB 343.0

Use instructions

- Levelling systems
- Hydro-pneumatic damping systems
- Electro-hydraulic roof controls
- Stabilisation and traction control systems
- Central locking systems

Observe manufacturer instructions!

TYPICAL PARAMETERS	METHODS	UNITS	ASTRON ZHF-M
Density at 15°C	DIN 51 757	kg/m ³	870
Viscosity at 40°C	DIN 51 562	mm ² /s	21
Viscosity at 100°C	DIN 51 562	mm ² /s	6,2
Viscosity index (VI)	DIN ISO 2909	-	280
Flash point COC	DIN ISO 2592	°C	130
Pour point	DIN ISO 3016	°C	- 51

* meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.

17.06.2025



Power in every molecule

Duran Lubricants & Chemicals GmbH
Rodderheide 3-7 • D-33824 Werther

Tel. +49 5203 901510
www.astron-oil.de
info@duran-oil.com

Health, Safety and Environment –
information is provided for products
in the relevant Safety Data Sheet.

