

ASTRON Galaxy Standard 5W-30

Synthetic High-Performance Low-Friction Engine Oil for Passenger Cars

Properties

Synthetic components combined with carefully selected innovative additives guarantee that the product meets the latest market requirements. Thanks to the significantly improved engine oil quality of **ASTRON Galaxy Standard 5W-30**, it offers further enhanced wear protection and keeps the engine perfectly clean. The extremely low cold viscosity of the lubricant and its reliable high-temperature viscosity properties guarantee significant reductions in fuel consumption.

Specifications:

- ACEA A3/B4
- API SN/CF

Recommendations *:

- MB 229.3
- BMW Longlife -01
- VW 502.00 / 505.00
- Opel GM-LL-A-025
- Opel GM-LL-B-025

Use instructions

ASTRON Galaxy Standard 5W-30 is the ideal high-performance low-friction engine oil for demanding engines. It is used in petrol and diesel engines in passenger cars, including models with turbocharger and direct injection. The product is recommended for all operating conditions.

TYPICAL PARAMETERS	METHODS	UNITS	ASTRON Galaxy Standard 5W-30
Density at 15°C	DIN 51 757	kg/m ³	855
Viscosity at -25°C	DIN 51 377	mPa.s	6150
Viscosity at 40°C	DIN 51 562	mm ² /s	70
Viscosity at 100°C	DIN 51 562	mm ² /s	11,8
Viscosity index (VI)	DIN ISO 2909	-	165
COC flash point	DIN ISO 2592	°C	238
Pour point	DIN ISO 3016	°C	- 42
Base number	DIN ISO 3771	mg KOH/g	10,4
Sulphated ash	DIN 51 575	g/100 g	1,4

* meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.

17.06.2025



Power in every molecule

Duran Lubricants & Chemicals GmbH
Rodderheide 3-7 • D-33824 Werther

Tel. +49 5203 901510
www.astron-oil.de
info@durand-oil.com

Health, Safety and Environment –
information is provided for products
in the relevant Safety Data Sheet.

