

## ASTRON Mehrzweckfett 2

### Multi-purpose lithium grease

#### Properties

- Mixable with most conventional soap base grease products.
- Good adhesive properties.
- Shear-proof and oxidation-resistant.
- Wear reducing.
- Water resistant.
- Prevents corrosion.

#### Use instructions

**ASTRON Mehrzweckfett 2** is particularly suitable for the lubrication of all types of anti-friction and plain bearings under normal load as well as joints operated at normal temperatures and conditions. This makes it a universal lubricant for automotive vehicles, construction machines and agricultural machinery.

When re-lubricating parts, ensure that the grease is not contaminated with dust or dirt particles.

**Observe manufacturer instructions!**

#### Specifications:

- DIN 51 5825: K2K-30
- ISO/DIS 6743-9: ISO-L-XCCHA 2

TYPICAL PARAMETERS	METHODS	UNITS	ASTRON Mehrzweckfett 2
NLGI grade	DIN 51 818	-	2
Soap/thickener	-	-	lithium soap
Colour	visuell	-	natural colour
Texture	visuell	-	flat
Operating temperature range	-	°C	-30 to + 120
Penetration	ISO 2137	0,1 mm	280-300
EMCOR - test	ISO 51 802	Rating	0-0
Drop point	DIN ISO 2176	°C	190
Viscosity (base oil) at 40°C	ASTM D 7042	mm <sup>2</sup> /s	100

\* meets the requirements of the OEM manufacturer.  
The stated values may vary within the usual commercial range.

17.06.2025



**Power in every molecule**

Duran Lubricants & Chemicals GmbH  
Rodderheide 3-7 • D-33824 Werther

Tel. +49 5203 901510  
www.astron-oil.de  
info@duran-oil.com

Health, Safety and Environment –  
information is provided for products  
in the relevant Safety Data Sheet.

