

# **ASTRON Galaxy LLi 5W-30**

## Synthetic high-performance low-viscosity engine oil for passenger cars

### **Properties**

**ASTRON Galaxy LLi 5W-30** is a synthetic high-performance fuelefficient engine oil of the SAE class 5W-30. Synthetic components and a matching innovative additives ensure compliance with the current practical requirements. The significantly improved engine oil quality of **ASTRON Galaxy LLi 5W-30** is especially reflected in the further improved wear protection and the improved engine cleanliness, even with extended oil change intervals. The extremely low low-temperature viscosity combined with a safe high-temperature viscosity ensures a high fuel-saving potential.

#### **Use instructions**

**ASTRON Galaxy LLi 5W-30** is suitable as a high-performance, low-friction engine oil for demanding engines. Recommended for passenger car petrol and diesel engines, including turbo versions and for direct injection engines, under all operating conditions.

#### **Specifications:**

- ACEA A3/B4
- API SN/CF

#### **Recommendations \*:**

- MB 229.3 / 229.5
- VW 502.00 / 505.00
- BMW Longlife-01
- Renault RN0700/RN0710
- Opel GM-LL-B-025
- Acura
- Chrysler
- Dodge
- Fiat
- Honda
- Hyundai
- Infiniti
- Kia
- Lexus
- Mazda
- Mitsubishi
- Nissan
- Subaru
- Toyota
- Haval
- CheryGeely
- BYD
- Dongfeng
- Jac
- Lifan

TYPICAL PARAMETERS	METHODS	UNITS	ASTRON Galaxy LLi 5W-30
SAE class	DIN 51 511	-	5W-30
Density at 15°C	DIN 51 757	kg/m³	855
Viscosity at 40°C	DIN 51 562	mm²/s	72,5
Viscosity at 100°C	DIN 51 562	mm²/s	12
Viscosity index (VI)	DIN ISO 2909	-	163
COC flash point	DIN ISO 2592	°C	240
Pour point	DIN ISO 3016	°C	- 39
Total base number	DIN ISO 3771	mg KOH/g	9,8
1			

<sup>\*</sup> meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.

17.06.2025



Power in every molecule

